

# PLASTISOLV 842

# ON PRESS CLEANER

PlastiSolv 842 On Press Cleaner is designed to remove plastisol ink from the screen printing mesh. This product evaporates quickly and should not be rinsed with water. 842 is to be used during on press color changes, saved screens, removing ink from squeegees, floodbars and other equipment.

# SPECIAL FEATURES:

- PlastiSolv 842 has a citrus odor which makes the job of color changes and screen reclaiming much more pleasant.
- PlastiSolv 842 dries safe, providing a safe, odor-free alternative to mineral spirits, aerosol screen opener and other hot, hazardous, flammable solvents.
- PlastiSolv 842 is non-flammable which makes it safer for handling, storage and rag disposal than conventional solvents.
- PlastiSolv 842 may be applied manually or recirculated through the EasiFlo System, or in an enclosed automatic screen washing system, providing superior product life and economy.

# APPLICATION FOR USF:

- Scrape all excess ink from screen.
- Apply PS 842 by squirt bottle, pnuematic sprayer or rag to the (well) ink side of the screen.
- Thoroughly agitate ink with a rag or a scrubber, then wipe up all dissolved ink.
- Reapply if necessary and follow with a dry rag, wipe on both sides of the screen.
- The screen will be ready for printing or tape application within 10-15 seconds.

# PHYSICAL AND CHEMICAL DATA:

#### **Appearance & Odor:**

Clear liquid with citrus

# **Specific Gravity:**

0.80 @ 20° C / 68° F

#### pH:

Neutral

#### VOC:

800 grams/liter

#### Flash Point:

61° C / 142° F

### **Ink Types:**

Plastisol

#### **Product Family:**

Textile